INTERIOR

BIOFA

Item no. 2049
New formula

Furniture Oil

solvent-free

150 ml - 375 ml - 1 l - 2,5 l - 10 l





As a primer and final coat, as well as for the care of furniture, interior fittings and toys. For absorbent surfaces made of wood.

- **Crystal Clear Ingredient Declaration (www.biofa.de)**
- **Low emission ***
- **Made with natural raw materials ****
- **98% renewable and mineral ingredients ****
- **Colorless**
- **Breathable and antistatic**
- **Dirt and water repellent**
- **complies with the requirements for QNG-Ready, qualification for KfW funding "Climate-friendly residential building/non-residential building"**

GEPRÜFT NACHHALTIGES PRODUKT
QNG READY
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu/pruefkriterien

ÉMISSIONS DANS L'AIR INTÉRIEUR*
A+
A+ A B C
RAUMLUFT EMISSIONEN*
* Angaben zum Emissionsgrad flüchtiger Stoffe in der Raumluft, die beim Einatmen ein Toxizitätsrisiko darstellen, auf einer Skala von A+ (sehr geringe Emissionen) bis C (hohe Emissionen)

Properties:

BIOFA furniture oil is a special boiling and mixture of natural oils, resins, bee, carnauba and rice husk wax. The oil has a greenish colour due to its high hemp oil content in the container, but this is no longer visible on the dried wood surface. It is suitable for all wooden surfaces in furniture and interior design. The oil penetrates well into the wood, revitalises and deepens the natural structure and tone of the treated wood and creates diffusible, resistant and antistatic surfaces.

** Ingredients:

Linseed oil, hemp oil, wood oil, soya oil, ricinseed oil-colophony resin, rice husk wax, beeswax, carnauba wax, matting agent, hydrophobing agent, defoamer, cobalt polymer drier, calcium and manganese drier, antioxidant.

97 per cent water and renewable raw materials
1 per cent mineral and metallic raw materials
2 per cent chemical-synthetic and fossil raw material

Processing steps:

1. Preparation Substrate must be dry (wood moisture content below 12%) and free of dirt and old paint coats. Finish sanding with 150 - 180 grit is recommended.
2. Base coat Remove any protective skin that may have formed; mix thoroughly. Apply with brush, lint-free rag, or sprayer. Polish to sheen with white pad or cloth after 30-50 minutes.
3. Topcoat A second coat after 6-12 hours will improve the finish quality.
4. Equipment cleaning Immediately after use, clean with BIOFA Brush Cleaner 0600 (solvent-free) or BIOFA Thinner 0500.
5. Care When required apply a small amount of furniture oil on a soft, lint-free rag, and apply an even, very thin coat. Then polish out the finish.

The information and instructions in the technical leaflet are binding. Prior consultation with the application engineering department of BIOFA is required if a deviation from these specifications is necessary. The generally accepted construction engineering practices must be observed. All previous information is null and void after the publication of this leaflet.
BIOFA Naturprodukte W. Hahn GmbH, Dobelstr. 22, D-73087 Bad Boll Germany, www.biofa-de.com, Tel. 07164-9405-0, Fax 07164-9405-96

INTERIOR

BIOFA


Item no.
2049
New formula

Important:

Be sure to test product before proceeding! Ensure sufficient fresh air circulation when processing and drying! Do not use below 16°C!

Recommended Equipment:






1. **009949 / 009934** Flat brush, professional quality 50 mm / 70 mm for oily-based porducts
2. **009951 / 009980** Varnish roller microfiber 100 mm / 180 mm
3. **009952 / 009996** Roller bracket 100 mm / 180 mm rollers
4. **009963 /009925** Pad green grit 180 Ø 150mm / pad brown Ø 150m with adhesive fleece for use by hand or with a polishing machine
5. **009974 / 009984** Pad white Ø 150mm / pad white with adhesive fleece Ø 150mm for buffing
6. **0600** BIOFA Brush Cleaner for cleaning the working equipment

Drying:

Dry and ready for overcoating after approx. 6-12 hrs. (20°C/ 50-55 % rel. humidity).
Fully cured and ready for unrestricted use after 7-10 days.

Consumption/yield per coat:

20-30 ml/m² or 35-50 m²/l, depending on absorption of the surface.

Storage:

Keep cool, dry and properly sealed. May form skin. Remove skin before next use. Screen oil as needed!

Container:

Glass bottle 150 ml
Coated metal containers 375 ml, 1 l, 2,5 l, 10 l

Disposal:

Deposit liquid product leftovers at collection point for old paints/ old varnishes, and/or dis-pose in compliance with local statutory regu-lations. Minor leftovers and soaked pro-cessing materials can be disposed in the household waste after drying out.
Only recycle fully emptied and cleaned con-tainers. Not completely emptied and cleaned containers must be treated and disposed like the product!

AVV waste code according to European waste list: 08 01 12

Hazard and safety information:

Store work materials and clothing soaked with product in an airtight metal container or soak in water and spread out on a non-flammable surface to dry - (risk of spontaneous combus-tion!) The product itself is not self-igniting.
Keep out of the reach of children. If medical advice is required, have packaging or labelling ready. Do not get in eyes, on skin or on clothing. In case of contact with skin, wash with plenty of soap and water. Ensure adequate skin protection! When spray-ing, do not inhale the spray mist and wear suitable respiratory protection (combination filter A2/P2) and safety goggles. Use respiratory protection (dust filter P2) when sanding. Do not allow to enter the sewage system, waterways or soil. A typical odour of the natural raw materials is possible.

Safety data sheet available on request

2049 contains max. 1 g/l VOC.

SHI product passport:

Healthy living - find products - certify buildings

All relevant product qualities regarding health compatibility and environmental impact of the product, which are required to achieve sustainable building certifications, can be found in the SHI product passport.

This QR code will take you to the SHI product passport for BIOFA Worktop Oil 2052:

The information and instructions in the technical leaflet are binding. Prior consultation with the application engineering department of BIOFA is required if a deviation from these specifications is necessary. The generally accepted construction engineering practices must be observed. All previous information is null and void after the publication of this leaflet.
BIOFA Naturprodukte W. Hahn GmbH, Dobelstr. 22, D-73087 Bad Boll Germany, www.biofa-de.com, Tel. 07164-9405-0, Fax 07164-9405-96